

# 2.8 Wagon

**FAT TRUCK**<sup>®</sup>  
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



**Zeal Motor Inc.**  
101, rue de la Production  
Cowansville, Quebec, Canada J2K 5H5  
579.319.0060  
sales@zealmotor.com  
[WWW.FATTRUCK.COM](http://WWW.FATTRUCK.COM)

# 2.8 Wagon

## SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload	2200 lb (1000 kg)	Make	Caterpillar	Front & Rear	FAT TRUCK® LGP 1640 x 640 x 610	Custom color	
Passengers capacity	8 (2 front + 6 rear)	Model	C2.2 Turbo diesel	Pressure	0.5 to 4.5 PSI (0.07 to 0.31BAR)	Front LED light bar	
Maximum speed on land	25 mph (40 km/h)	Emission standards	EPA Tier 4 Final EU Stage V	Pressure control	Automatic pressure control	Rear LED Light bar	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	4 cylinders	<b>FUEL SYSTEM</b>		Side working LED lights front	
Maximum uphill & downhill	35°/ 70%	Displacement	135 po³ (2.22 L)	Capacity	21 US Gal (80 L)	Side working LED lights rear	
Maximum sidehill	22°/ 40%	Horsepower @ 2800 RPM	74 hp (55 kW)	Average fuel autonomy	12 h	4 corner LED beacon amber lights	
Turning radius	0°	Torque @ 1400 RPM	199 lb-ft (270 N-m)	<b>STANDARD EQUIPMENT</b>		Search light	
Shipping weight	5440 lb (2443 kg)	Cooling System	Liquid cooled	Doors	Lockable	Inclinometer with alarm	
Ground pressure fully loaded	1.6 lb/po² (0.11 kg/cm²)	<b>ELECTRICAL</b>		Operator seats	2 front seats with 3-points seat belts	Backup camera	
<b>SAFETY FEATURES</b>		Voltage	12 V	Lights	Front, brakes, position, flashers, dome	4-way backup camera	
ROPS	ISO 3471	Alternator capacity	275 A	Horn	Electric	Backup alarm	
EPA	Stage V	Battery capacity	960 CCA	Ingress	Front ladder with grab handles	Front mirrors	
Brakes	Automatic safety brake	Battery type	AGM	Standard color	Red or white	Air conditioning	
<b>DIMENSIONS</b>		<b>TRANSMISSION</b>		Fire extinguisher	2.5 lb ABC	35 000 BTU cab heater	
Height	101 in (2565 mm)	Type	Hydrostatic	4 sliding side windows		Front feet heater	
Length	146.5 in (3720 mm)	Final drive	Carbon fiber synchronous belts	Bilge pump		Fuel cab heater	
Width	100 in (2540 mm)	<b>BRAKES</b>		Cup holders		Ventilation Fans	
Ground clearance	20.7 in (526 mm)	Brakes	Positive deceleration through hydrostatic transmission	First aid kit		Fuel heater for engine water and transmission oil	
<b>CONTROLS</b>		Parking brakes	Brake disc applied pressure released	Front and rear bumpers		110V heater cold engine water and transmission oil	
Controllor	Microprocessor			Lockable fuel cap		Rear seats with 2 pts safety belts	
Steering	Joystick			Operator & Maintenance manual		Rear seats with 3 pts safety belts	
Display	Color display					4-forward facing seats	
<b>WARRANTY</b>						Roof Rack with side ladder	
Limited 1 year / 1000 hours (Which ever comes first)						Radio Bluetooth	
						Rear hitch receiver	
						Pintle hook	
						Additional battery	
						Front winch	
						D rings	
						Wheel Pods™	
						Studs for ice	
						Rear capstan winch	
						Hot sticks storage tubes	
						Ladder rack	
						Storage box	

