

FT3 WAGON

FATXTRUCK®
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



WE'LL GET YOU THERE™

**ZEAL
MOTOR**

101, rue de la Production
Cowansville, Quebec, Canada J2K 5H5
579.319.0060 | sales@zealmotor.com

WWW.FATTRUCK.COM

FT3 WAGON

SPECIFICATIONS

PERFORMANCE

| | |
|------------------------------|---|
| Payload on land | 3000 lb (1357 kg) |
| Payload on water | 2200 lb (998 kg) |
| Passenger capacity | 8 (2 front + 6 rear) |
| Maximum speed on land | 25 mph (40 km/h) |
| Maximum speed on water | 3.1 mph (5 km/h) |
| Maximum uphill & downhill | 35° / 70% |
| Maximum sidehill | 22° / 40% |
| Turning radius | 0° |
| Base weight | 6900 lb (3122 kg) |
| Ground pressure fully loaded | 1.6 lb/po ² (0.11 kg/cm ²) |

SAFETY FEATURES

| | |
|--------|------------------------|
| ROPS | ISO 3471 |
| EPA | Stage V |
| Brakes | Automatic safety brake |

DIMENSIONS

| | |
|------------------------------|--------------------|
| Height with roof rack | 109 in (2763 mm) |
| Height with air conditioning | 115.2 in (2927 mm) |
| Length | 147 in (3730 mm) |
| Width | 100 in (2540 mm) |
| Ground clearance | 25.5 in (650 mm) |

CONTROLS

| | |
|------------|----------------|
| Controller | Microprocessor |
| Steering | Joystick |
| Display | Color display |

WARRANTY

Limited 1 year / 1000 hours (Whichever comes first)

ENGINE

| | |
|---------------------|----------------------------------|
| Make | HATZ |
| Model | 4H50TICD |
| Emission standards | EPA Tier 4 Final EURO Stage V |
| Number of cylinders | 4 cylinders |
| Displacement | 1.95 L |
| Horsepower | 74 hp (55 kW) |
| Torque @ 1400 RPM | 177 lb-ft (240 N-m) |
| Cooling system | Liquid cooled |

ELECTRICAL

| | |
|---------------------|---------|
| Voltage | 12 V |
| Alternator capacity | 370 A |
| Battery capacity | 960 CCA |
| Battery type | AGM |

TRANSMISSION

| | |
|-------------|--------------------|
| Type | Hydrostatic |
| Final drive | 4 Hydraulic motors |

BRAKES

| | |
|----------------|--|
| Brakes | Positive deceleration through hydrostatic transmission |
| Parking brakes | Brake disc applied pressure released |

TIRES

| | |
|------------------|-----------------------------------|
| Front & Rear | FAT TRUCK® LGP 68 x 24 x 24 in |
| Pressure | 0.5 to 4.5 PSI (0.07 to 0.31 BAR) |
| Pressure control | Automatic pressure control |

FUEL SYSTEM

| | |
|-----------------------|------------------|
| Capacity | 22 US Gal (83 L) |
| Average fuel autonomy | 12 h |

STANDARD EQUIPMENT

Standard color: Red or white
Lockable doors
2 front seats with 3-points seat belts
4 sliding side windows with bug screen
Lights: Front, brakes, position, flashers, dome
4 corner LED beacon amber lights
Backup alarm
Front mirrors
Front and rear bumpers with hitch
Front and rear ladder with grab handles
Rear roof rack with side ladder
Electric horn
Inclinometer with alarm
Backup camera or 4-way backup camera
Master cut-off switch
Cup holders
3 x 12 V charging ports
Lockable fuel cap
D rings
Bilge pump
Wheel Pods™
Fire extinguisher 2.5 lb ABC
First aid kit
Operator & Maintenance manual

OPTIONS

Custom color
Front LED light bar
Rear LED light bar
Side working LED lights front and rear
Search light
Air conditioning
Ventilation fans
35 000 BTU cab heater
Front feet heater
Fuel cab heater
Fuel heater for engine water and transmission oil
110 V heater cold engine water and transmission oil
Rear seats with 2 pts safety belts
Rear seats with 3 pts safety belts
4-forward facing seats
Additional battery
Front, rear winch
Rear capstan winch
Studs for ice
Hot sticks storage tubes
Ladder rack
Storage box
Pintle hook
Radio Bluetooth®

